

IASI L0 and L1 Daily Monitoring Report **Metop-B**

IASI monitoring team

28/04/2022 00:00:00 - 29/04/2022 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-B satellite retrieved from the IASI L0 and L1 ENG product (3 minutes data packet) for 28/04/2022 00:00:00 - 29/04/2022 00:00:00 .

The monitoring data are extracted on PDU basis.

2 Data quantity 28/04/2022 00:00:00 - 29/04/2022 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	449	e
L0 IASI PDUs	449	e
L1 ENG PDUs	448	e
L1 ENG distinct GEPSGranule	430	a
L1 DPX PDUs (RM: IASI-HIRS)	2	e
L1 DPS Files (RM: OBS-CAL NWP based)	298	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	5646	910	20220428081221.210	20220428090408.459
PX1 (130)	2211	13293	20220428113532.528	20220428122448.660
PX2 (135)	5646	910	20220428081221.210	20220428090408.459
PX2 (135)	2210	13293	20220428113532.309	20220428122448.660
PX3 (140)	5646	910	20220428081221.210	20220428090408.459
PX3 (140)	2210	13293	20220428113532.309	20220428122448.660
PX4 (145)	5646	910	20220428081221.210	20220428090408.459
PX4 (145)	2210	13293	20220428113532.309	20220428122448.660
IMG (150)	15133	11950	20220428081220.995	20220428090407.163
IMG (150)	1410	13973	20220428113532.309	20220428122448.660
VER (160)	11859	13805	20220428081214.706	20220428090414.729
VER (160)	3095	4946	20220428113526.688	20220428122454.715
AUX (180)	2371	2760	20220428081215.136	20220428090407.163
AUX (180)	3895	4266	20220428113527.122	20220428122455.148

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
28/04/2022 00:00:04	-	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	449	e
L1 ENG PDUs	448	e
L1 ENG distinct GEPSGranule	430	a
GQisFlagQual set (PX1)	99.52 %	-
GQisFlagQual set (PX2)	99.62 %	-
GQisFlagQual set (PX3)	99.60 %	-
GQisFlagQual set (PX4)	99.53 %	-
GQisFlagQual set (all)	99.57 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: Timeseries of flag of Over and Under Flows

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class).

A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T, water vapor and Ozone. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used.

Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 28 to 34, the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixels and scan positions 10 to 20) and the average bias OBS-CAL (over all pixels and scan positions 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BT: All Channels




Figure 11: Radiance Anomaly in BT: IASI Band 1




Figure 12: Radiance Anomaly in BT: IASI Band 2




Figure 13: Radiance Anomaly in BT: IASI Band 3




Figure 14: Radiance Anomaly in BT: CO2 14




Figure 15: Radiance Anomaly in BT: CO2 4.3




Figure 16: Radiance Anomaly in BT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board Metop is performed on all pixels with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference NeDT. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.



Figure 17: Radiance Differences in BT



Figure 18: Radiance Differences in BT




Figure 19: Radiance Differences in BT




Figure 20: Radiance Differences in BT




Figure 21: Radinace Differences in BT