

IASI L0 and L1 Weekly Monitoring Report

IASI monitoring team

09/01/2023 00:00:00 - 16/01/2023 00:00:00 (Week 02)

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-C satellite retrieved from the IASI L0 and L1 ENG product (3 minute data packet) for 09/01/2023 00:00:00 - 16/01/2023 00:00:00 .

The monitoring data are extracted on PDU basis.

Data extraction, calibration, processing and statistics are performed at EUMETSAT.

2 Data quantity 09/01/2023 00:00:00 - 16/01/2023 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	3361	-
L0 IASI PDUs	3361	-
L1 ENG PDUs	3360	-
L1 ENG distinct GEPSGranule	3360	-
L1 DPX PDUs (RM: IASI-HIRS)	0	e
L1 DPS Files (RM: OBS-CAL NWP based)	3360	-

Table 1: Data quantity

APID	Packet type	Packets lost
-	-	-

Table 2: L0 packet losses

3 Instrument modes

Time	Transition from	Transition to
09/01/2023 00:02:12	-	Normal operation
10/01/2023 21:40:36	Auxiliary ASE synchronised	External calibration
10/01/2023 22:01:08	External calibration	Auxiliary ASE synchronised
10/01/2023 22:03:00	Auxiliary ASE synchronised	Normal operation
10/01/2023 23:20:52	Auxiliary ASE synchronised	External calibration
10/01/2023 23:44:36	External calibration	Auxiliary ASE synchronised
10/01/2023 23:46:44	Auxiliary ASE synchronised	Normal operation
11/01/2023 01:29:08	External calibration	Auxiliary ASE synchronised
11/01/2023 01:31:16	Auxiliary ASE synchronised	Normal operation
11/01/2023 05:01:08	External calibration	Auxiliary ASE synchronised
11/01/2023 05:03:16	Auxiliary ASE synchronised	Normal operation
11/01/2023 07:03:16	External calibration	Auxiliary ASE synchronised
11/01/2023 07:05:24	Auxiliary ASE synchronised	Normal operation
11/01/2023 08:45:24	External calibration	Auxiliary ASE synchronised
11/01/2023 08:47:32	Auxiliary ASE synchronised	Normal operation
11/01/2023 09:35:48	Auxiliary ASE synchronised	External calibration
11/01/2023 10:28:04	External calibration	Auxiliary ASE synchronised
11/01/2023 10:29:56	Auxiliary ASE synchronised	Normal operation
11/01/2023 11:20:04	Normal operation	Auxiliary ASE synchronised
11/01/2023 12:11:16	External calibration	Auxiliary ASE synchronised
11/01/2023 12:13:08	Auxiliary ASE synchronised	Normal operation
11/01/2023 13:07:00	Normal operation	Auxiliary ASE synchronised
11/01/2023 13:09:08	Auxiliary ASE synchronised	External calibration
11/01/2023 13:55:32	External calibration	Auxiliary ASE synchronised
11/01/2023 13:57:40	Auxiliary ASE synchronised	Normal operation
11/01/2023 14:53:24	Normal operation	Auxiliary ASE synchronised
11/01/2023 14:55:32	Auxiliary ASE synchronised	External calibration
11/01/2023 15:41:40	External calibration	Auxiliary ASE synchronised
11/01/2023 15:43:32	Auxiliary ASE synchronised	Normal operation
11/01/2023 17:04:36	Normal operation	Auxiliary ASE synchronised
11/01/2023 17:06:28	Auxiliary ASE synchronised	External calibration
11/01/2023 17:28:20	External calibration	Auxiliary ASE synchronised
11/01/2023 17:30:28	Auxiliary ASE synchronised	Normal operation
11/01/2023 18:47:32	Normal operation	Auxiliary ASE synchronised
11/01/2023 18:49:40	Auxiliary ASE synchronised	External calibration
11/01/2023 19:16:52	Auxiliary ASE synchronised	Normal operation
11/01/2023 20:29:56	Normal operation	Auxiliary ASE synchronised
11/01/2023 20:32:04	Auxiliary ASE synchronised	External calibration
11/01/2023 21:00:36	External calibration	Auxiliary ASE synchronised
11/01/2023 21:02:28	Auxiliary ASE synchronised	Normal operation
11/01/2023 22:12:04	Normal operation	Auxiliary ASE synchronised
11/01/2023 22:13:56	Auxiliary ASE synchronised	External calibration
11/01/2023 22:45:08	External calibration	Auxiliary ASE synchronised
11/01/2023 22:47:16	Auxiliary ASE synchronised	Normal operation
11/01/2023 23:53:56	Normal operation	Auxiliary ASE synchronised
11/01/2023 23:55:48	Auxiliary ASE synchronised	External calibration
12/01/2023 00:26:12	External calibration	Auxiliary ASE synchronised
12/01/2023 00:28:04	Auxiliary ASE synchronised	Normal operation
12/01/2023 01:35:32	Normal operation	Auxiliary ASE synchronised
12/01/2023 01:37:40	Auxiliary ASE synchronised	External calibration
12/01/2023 02:08:36	Auxiliary ASE synchronised	Normal operation
12/01/2023 03:19:47	Normal operation	Auxiliary ASE synchronised
12/01/2023 03:21:55	Auxiliary ASE synchronised	External calibration

Continued on next page

Table 3 – continued from previous page

Time	Transition from	Transition to
12/01/2023 05:06:59	Auxiliary ASE synchronised	External calibration

Table 3: Instrument modes

4 L0 and L1 Data Quality

Day	L0 quality	L1 quality	L0 PDUs	L1 PDUs
09/01/2023	99.60 %	99.59 %	480	480
10/01/2023	99.59 %	99.53 %	480	480
11/01/2023	97.72 %	95.28 %	480	480
12/01/2023	99.45 %	98.97 %	480	480
13/01/2023	99.62 %	99.62 %	480	480
14/01/2023	99.61 %	99.61 %	480	480
15/01/2023	99.62 %	99.62 %	480	480

Table 4: Quality overview




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 1C quality




Figure 4: OverUnderFlowFlag timeseries

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class). A radiative transfer model (RTM) is fed with co-located ECMWF profiles of T,WV, and Ozon. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After the 18th of May 2010 the RTTOV model in V9.3 is used. Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only).




Figure 5: Average radiance differences: OBS-CAL




Figure 6: Average radiance differences: OBS-CAL




Figure 7: Standard deviation of radiance differences




Figure 8: Standard deviation of radiance differences per pixel




Figure 9: Radiance bias in BRT: All Channels




Figure 10: Radiance bias in BRT: IASI Band 1




Figure 11: Radiance bias in BRT: IASI Band 2




Figure 12: Radiance bias in BRT: IASI Band 3




Figure 13: Radiance bias in BRT: CO2 14




Figure 14: Radiance bias in BRT: CO2 4.3




Figure 15: Radiance bias in BRT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board Metop-C is performed on all pixel with distances smaller than 3 km between IASI and HIRS. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference temperature.




Figure 16: Radiance Differences in BRT 1h Average




Figure 17: Standard Deviation of Radiance Differences 1h Average




Figure 18: Radiance Differences in BRT 1h Average - Clear Sky



Figure 19: Standard Deviation of Radiance Differences 1h Average - Clear Sky