

IASI L0 and L1 Daily Monitoring Report

IASI monitoring team

20/09/2013 00:00:00 - 21/09/2013 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the MetOp-B satellite retrieved from the IASI L0 and L1 ENG product (3 minute data packet) for 20/09/2013 00:00:00 - 21/09/2013 00:00:00 .

The monitoring data are extracted on PDU basis.

Data extraction, calibration, processing and statistics are performed at EUMETSAT.

2 Data quantity 20/09/2013 00:00:00 - 21/09/2013 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	481	-
L1 DPX PDUs (RM: IASI-HIRS)	480	-
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	8143	8203	20130920130242.163	20130920130258.163
PX1 (130)	8203	8364	20130920130258.163	20130920130342.053
PX1 (130)	8372	8375	20130920130343.784	20130920130344.432
PX2 (135)	8142	8192	20130920130241.948	20130920130255.784
PX2 (135)	8192	8203	20130920130255.784	20130920130258.163
PX2 (135)	8203	8364	20130920130258.163	20130920130342.053
PX2 (135)	8372	8375	20130920130343.784	20130920130344.432
PX3 (140)	8142	8192	20130920130241.948	20130920130255.784
PX3 (140)	8192	8203	20130920130255.784	20130920130258.163
PX3 (140)	8203	8364	20130920130258.163	20130920130342.053
PX3 (140)	8371	8375	20130920130343.569	20130920130344.432
PX4 (145)	8142	8181	20130920130241.948	20130920130253.409
PX4 (145)	8181	8192	20130920130253.409	20130920130255.784
PX4 (145)	8192	8203	20130920130255.784	20130920130258.163
PX4 (145)	8203	8364	20130920130258.163	20130920130342.053
PX4 (145)	8371	8375	20130920130343.569	20130920130344.432
IMG (150)	2010	2057	20130920130241.948	20130920130253.409
IMG (150)	2057	2068	20130920130253.409	20130920130255.784

Continued on next page

Table 2 – continued from previous page

APID	Seq from	Seq to	Time from	Time to
IMG (150)	2068	2264	20130920130255.784	20130920130342.053
IMG (150)	2271	2275	20130920130343.569	20130920130344.432
VER (160)	634	675	20130920130234.815	20130920130346.811
AUX (180)	6658	6667	20130920130235.245	20130920130347.241

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
20/09/2013 00:00:08	-	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	481	-
GQisFlagQual set (PX1)	99.52 %	-
GQisFlagQual set (PX2)	99.59 %	-
GQisFlagQual set (PX3)	99.59 %	-
GQisFlagQual set (PX4)	99.52 %	-
GQisFlagQual set (all)	99.56 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: OverUnderFlowFlag timeseries

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class). A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T,WV, and Ozon. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used. Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 10 to 16 the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixel and scan position 10 to 20) and the average bias OBS-CAL (over all pixel and scan position 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BRT: All Channels




Figure 11: Radiance Anomaly in BRT: IASI Band 1




Figure 12: Radiance Anomaly in BRT: IASI Band 2




Figure 13: Radiance Anomaly in BRT: IASI Band 3




Figure 14: Radiance Anomaly in BRT: CO2 14




Figure 15: Radiance Anomaly in BRT: CO2 4.3




Figure 16: Radiance Anomaly in BRT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board MetOp is performed on all pixel with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference temperature. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.




Figure 17: Radiance Differences in BRT




Figure 18: Radiance Differences in BRT




Figure 19: Radiance Differences in BRT




Figure 20: Radiance Differences in BRT




Figure 21: Radinace Differences in BRT