

IASI L0 and L1 Daily Monitoring Report

IASI monitoring team

21/11/2013 00:00:00 - 22/11/2013 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the MetOp-B satellite retrieved from the IASI L0 and L1 ENG product (3 minute data packet) for 21/11/2013 00:00:00 - 22/11/2013 00:00:00 .

The monitoring data are extracted on PDU basis.

Data extraction, calibration, processing and statistics are performed at EUMETSAT.

2 Data quantity 21/11/2013 00:00:00 - 22/11/2013 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	481	-
L0 IASI PDUs	466	-
L1 ENG PDUs	464	-
L1 ENG distinct GEPSGranule	465	-
L1 DPX PDUs (RM: IASI-HIRS)	463	-
L1 DPS Files (RM: OBS-CAL NWP based)	464	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	4175	0	20131121123305.804	20131121132211.530
PX2 (135)	4175	0	20131121123305.804	20131121132211.530
PX3 (140)	4175	0	20131121123305.804	20131121132211.530
PX4 (145)	4175	0	20131121123305.804	20131121132211.530
IMG (150)	9819	0	20131121123305.804	20131121132211.530
VER (160)	7173	2550	20131121123305.804	20131121143049.792
VER (160)	2550	2555	20131121143049.792	20131121143049.792
VER (160)	2555	2560	20131121143049.792	20131121143049.792
VER (160)	2560	2565	20131121143049.792	20131121143049.792
VER (160)	2565	2570	20131121143049.792	20131121143049.792
VER (160)	2570	2551	20131121143049.792	20131121143049.792
VER (160)	2551	2556	20131121143049.792	20131121143049.792
VER (160)	2556	2561	20131121143049.792	20131121143049.792
VER (160)	2561	2566	20131121143049.792	20131121143049.792
VER (160)	2566	2571	20131121143049.792	20131121143049.792
VER (160)	2571	2552	20131121143049.792	20131121143049.792
VER (160)	2552	2557	20131121143049.792	20131121143049.792
VER (160)	2557	2562	20131121143049.792	20131121143049.792

Continued on next page

Table 2 – continued from previous page

APID	Seq from	Seq to	Time from	Time to
VER (160)	2562	2567	20131121143049.792	20131121143049.792
VER (160)	2567	2572	20131121143049.792	20131121143049.792
VER (160)	2572	2553	20131121143049.792	20131121143049.792
VER (160)	2553	2558	20131121143049.792	20131121143049.792
VER (160)	2558	2563	20131121143049.792	20131121143049.792
VER (160)	2563	2568	20131121143049.792	20131121143049.792
VER (160)	2568	2573	20131121143049.792	20131121143049.792
VER (160)	2573	2554	20131121143049.792	20131121143049.792
VER (160)	2554	2559	20131121143049.792	20131121143049.792
VER (160)	2559	2564	20131121143049.792	20131121143049.792
VER (160)	2564	2569	20131121143049.792	20131121143049.792
VER (160)	2569	2574	20131121143049.792	20131121143049.792
AUX (180)	1410	0	20131121123258.234	20131121132218.233

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
21/11/2013 00:00:15	-	Normal operation
21/11/2013 12:33:19	Normal operation	Auxiliary ASE synchronised
21/11/2013 12:34:07	Auxiliary ASE synchronised	Heater 2
21/11/2013 12:35:11	Heater 2	Heater 1 warm up
21/11/2013 12:36:15	Heater 1 warm up	Heater 2
21/11/2013 13:22:07	Auxiliary ASE synchronised	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	466	-
L1 ENG PDUs	464	-
L1 ENG distinct GEPSGranule	465	-
GQisFlagQual set (PX1)	99.60 %	-
GQisFlagQual set (PX2)	99.67 %	-
GQisFlagQual set (PX3)	99.70 %	-
GQisFlagQual set (PX4)	99.65 %	-
GQisFlagQual set (all)	99.66 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: OverUnderFlowFlag timeseries

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class). A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T,WV, and Ozon. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used. Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 10 to 16 the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixel and scan position 10 to 20) and the average bias OBS-CAL (over all pixel and scan position 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BRT: All Channels




Figure 11: Radiance Anomaly in BRT: IASI Band 1




Figure 12: Radiance Anomaly in BRT: IASI Band 2




Figure 13: Radiance Anomaly in BRT: IASI Band 3




Figure 14: Radiance Anomaly in BRT: CO2 14




Figure 15: Radiance Anomaly in BRT: CO2 4.3




Figure 16: Radiance Anomaly in BRT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board MetOp is performed on all pixel with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference temperature. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.




Figure 17: Radiance Differences in BRT




Figure 18: Radiance Differences in BRT




Figure 19: Radiance Differences in BRT




Figure 20: Radiance Differences in BRT




Figure 21: Radinace Differences in BRT