

IASI L0 and L1 Daily Monitoring Report

IASI monitoring team

19/03/2018 00:00:00 - 20/03/2018 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the MetOp-B satellite retrieved from the IASI L0 and L1 ENG product (3 minute data packet) for 19/03/2018 00:00:00 - 20/03/2018 00:00:00 .

The monitoring data are extracted on PDU basis.

Data extraction, calibration, processing and statistics are performed at EUMETSAT.

2 Data quantity 19/03/2018 00:00:00 - 20/03/2018 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	469	-
L1 DPX PDUs (RM: IASI-HIRS)	480	-
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	5197	5291	20180319003003.667	20180319003028.531
PX1 (130)	5294	5370	20180319003029.179	20180319003048.640
PX1 (130)	3485	3813	20180319111748.488	20180319111916.050
PX1 (130)	3917	3919	20180319111943.077	20180319111943.511
PX2 (135)	5197	5291	20180319003003.667	20180319003028.531
PX2 (135)	5294	5370	20180319003029.179	20180319003048.640
PX2 (135)	3485	3813	20180319111748.488	20180319111916.050
PX3 (140)	5197	5291	20180319003003.667	20180319003028.531
PX3 (140)	5294	5370	20180319003029.179	20180319003048.640
PX3 (140)	3485	3813	20180319111748.488	20180319111916.050
PX4 (145)	5196	5291	20180319003003.449	20180319003028.531
PX4 (145)	5294	5369	20180319003029.179	20180319003048.421
PX4 (145)	3485	3813	20180319111748.488	20180319111916.050
IMG (150)	15596	15703	20180319003003.449	20180319003028.531
IMG (150)	15705	15789	20180319003028.964	20180319003048.421
IMG (150)	549	920	20180319111748.488	20180319111915.835
VER (160)	793	819	20180319003000.855	20180319003048.855
VER (160)	8699	8755	20180319111744.808	20180319111920.808

Continued on next page

Table 2 – continued from previous page

APID	Seq from	Seq to	Time from	Time to
AUX (180)	6695	6701	20180319003001.289	20180319003049.289
AUX (180)	11553	11565	20180319111745.242	20180319111921.238

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
19/03/2018 00:01:34	-	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	469	-
GQisFlagQual set (PX1)	99.64 %	-
GQisFlagQual set (PX2)	99.70 %	-
GQisFlagQual set (PX3)	99.68 %	-
GQisFlagQual set (PX4)	99.61 %	-
GQisFlagQual set (all)	99.66 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: OverUnderFlowFlag timeseries

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class). A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T,WV, and Ozon. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used. Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 10 to 16 the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixel and scan position 10 to 20) and the average bias OBS-CAL (over all pixel and scan position 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BRT: All Channels




Figure 11: Radiance Anomaly in BRT: IASI Band 1




Figure 12: Radiance Anomaly in BRT: IASI Band 2




Figure 13: Radiance Anomaly in BRT: IASI Band 3




Figure 14: Radiance Anomaly in BRT: CO2 14




Figure 15: Radiance Anomaly in BRT: CO2 4.3




Figure 16: Radiance Anomaly in BRT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board MetOp is performed on all pixel with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference temperature. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.




Figure 17: Radiance Differences in BRT




Figure 18: Radiance Differences in BRT




Figure 19: Radiance Differences in BRT




Figure 20: Radiance Differences in BRT




Figure 21: Radinace Differences in BRT