

IASI L0 and L1 Daily Monitoring Report

IASI monitoring team

30/07/2010 00:00:00 - 31/07/2010 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the MetOp-A satellite retrieved from the IASI L0 and L1 ENG product (3 minute data packet) for 30/07/2010 00:00:00 - 31/07/2010 00:00:00 .

The monitoring data are extracted on PDU basis.

Data extraction, calibration, processing and statistics are performed at EUMETSAT.

2 Data quantity 30/07/2010 00:00:00 - 31/07/2010 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	481	-
L1 DPX PDUs (RM: IASI-HIRS)	439	e
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	4410	4412	20100730191056.422	20100730191056.856
PX1 (130)	4433	4461	20100730191103.559	20100730191111.774
PX1 (130)	4462	4464	20100730191111.989	20100730191112.422
PX1 (130)	4468	4470	20100730191113.286	20100730191115.879
PX2 (135)	4411	4413	20100730191056.641	20100730191057.071
PX2 (135)	4433	4461	20100730191103.559	20100730191111.774
PX2 (135)	4462	4464	20100730191111.989	20100730191112.422
PX2 (135)	4468	4470	20100730191113.286	20100730191115.879
PX3 (140)	4412	4414	20100730191056.856	20100730191057.286
PX3 (140)	4433	4461	20100730191103.559	20100730191111.774
PX3 (140)	4468	4470	20100730191113.286	20100730191115.879
PX4 (145)	4412	4414	20100730191056.856	20100730191057.286
PX4 (145)	4414	4416	20100730191057.286	20100730191059.883
PX4 (145)	4433	4461	20100730191103.559	20100730191111.774
PX4 (145)	4461	4463	20100730191111.774	20100730191112.207
PX4 (145)	4468	4470	20100730191113.286	20100730191115.879
IMG (150)	2547	2549	20100730191056.856	20100730191057.286
IMG (150)	2572	2603	20100730191103.559	20100730191111.559

Continued on next page

Table 2 – continued from previous page

APID	Seq from	Seq to	Time from	Time to
IMG (150)	2604	2606	20100730191111.774	20100730191112.207
IMG (150)	2610	2617	20100730191113.071	20100730191115.879
VER (160)	1863	1874	20100730191057.504	20100730191121.504
AUX (180)	3629	3632	20100730191058.153	20100730191122.153

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
30/07/2010 00:00:05	-	Normal operation
30/07/2010 17:24:21	Normal operation	Auxiliary ASE synchronised
30/07/2010 17:52:53	External calibration	Auxiliary ASE synchronised
30/07/2010 17:55:01	Auxiliary ASE synchronised	Normal operation
30/07/2010 19:04:37	Normal operation	Auxiliary ASE synchronised
30/07/2010 19:33:41	External calibration	Auxiliary ASE synchronised
30/07/2010 19:35:49	Auxiliary ASE synchronised	Normal operation
30/07/2010 20:44:37	Normal operation	Auxiliary ASE synchronised
30/07/2010 21:14:13	External calibration	Auxiliary ASE synchronised
30/07/2010 21:16:21	Auxiliary ASE synchronised	Normal operation
30/07/2010 22:24:37	Normal operation	Auxiliary ASE synchronised
30/07/2010 22:26:29	Auxiliary ASE synchronised	External calibration
30/07/2010 22:54:45	External calibration	Auxiliary ASE synchronised
30/07/2010 22:56:53	Auxiliary ASE synchronised	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSSGranule	481	-
GQisFlagQual set (PX1)	97.98 %	-
GQisFlagQual set (PX2)	97.66 %	-
GQisFlagQual set (PX3)	97.51 %	-
GQisFlagQual set (PX4)	97.91 %	-
GQisFlagQual set (all)	97.77 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: OverUnderFlowFlag timeseries

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class). A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T,WV, and Ozon. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used. Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 10 to 16 the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixel and scan position 10 to 20) and the average bias OBS-CAL (over all pixel and scan position 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BRT: All Channels




Figure 11: Radiance Anomaly in BRT: IASI Band 1




Figure 12: Radiance Anomaly in BRT: IASI Band 2




Figure 13: Radiance Anomaly in BRT: IASI Band 3




Figure 14: Radiance Anomaly in BRT: CO2 14




Figure 15: Radiance Anomaly in BRT: CO2 4.3




Figure 16: Radiance Anomaly in BRT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board MetOp is performed on all pixel with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference temperature. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.




Figure 17: Radiance Differences in BRT




Figure 18: Radiance Differences in BRT




Figure 19: Radiance Differences in BRT




Figure 20: Radiance Differences in BRT




Figure 21: Radinace Differences in BRT