

IASI L0 and L1 Daily Monitoring Report

IASI monitoring team

06/09/2012 00:00:00 - 07/09/2012 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the MetOp-A satellite retrieved from the IASI L0 and L1 ENG product (3 minute data packet) for 06/09/2012 00:00:00 - 07/09/2012 00:00:00 .

The monitoring data are extracted on PDU basis.

Data extraction, calibration, processing and statistics are performed at EUMETSAT.

2 Data quantity 06/09/2012 00:00:00 - 07/09/2012 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSSGranule	481	-
L1 DPX PDUs (RM: IASI-HIRS)	480	-
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	4912	4918	20120906164141.229	20120906164144.041
PX1 (130)	4955	5100	20120906164153.553	20120906164232.471
PX1 (130)	5144	5151	20120906164243.498	20120906164245.014
PX2 (135)	4912	4917	20120906164141.229	20120906164143.823
PX2 (135)	4955	5100	20120906164153.553	20120906164232.471
PX2 (135)	5143	5150	20120906164243.283	20120906164244.795
PX3 (140)	4912	4917	20120906164141.229	20120906164143.823
PX3 (140)	4955	5100	20120906164153.553	20120906164232.471
PX3 (140)	5143	5150	20120906164243.283	20120906164244.795
PX4 (145)	4912	4917	20120906164141.229	20120906164143.823
PX4 (145)	4955	5100	20120906164153.553	20120906164232.471
PX4 (145)	5143	5150	20120906164243.283	20120906164244.795
IMG (150)	8716	8725	20120906164141.229	20120906164143.823
IMG (150)	8766	8932	20120906164153.338	20120906164232.471
IMG (150)	8979	8986	20120906164243.283	20120906164244.795
VER (160)	12977	12980	20120906164141.229	20120906164149.229
VER (160)	12984	13010	20120906164149.229	20120906164237.229
AUX (180)	9142	9144	20120906164133.663	20120906164149.662

Continued on next page

Table 2 – continued from previous page

APID	Seq from	Seq to	Time from	Time to
AUX (180)	9144	9150	20120906164149.662	20120906164237.662

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
06/09/2012 00:00:04	-	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	481	-
GQisFlagQual set (PX1)	99.41 %	-
GQisFlagQual set (PX2)	99.32 %	-
GQisFlagQual set (PX3)	99.35 %	-
GQisFlagQual set (PX4)	99.44 %	-
GQisFlagQual set (all)	99.38 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: OverUnderFlowFlag timeseries

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class). A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T,WV, and Ozon. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used. Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 10 to 16 the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixel and scan position 10 to 20) and the average bias OBS-CAL (over all pixel and scan position 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BRT: All Channels




Figure 11: Radiance Anomaly in BRT: IASI Band 1




Figure 12: Radiance Anomaly in BRT: IASI Band 2




Figure 13: Radiance Anomaly in BRT: IASI Band 3




Figure 14: Radiance Anomaly in BRT: CO2 14




Figure 15: Radiance Anomaly in BRT: CO2 4.3




Figure 16: Radiance Anomaly in BRT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board MetOp is performed on all pixel with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference temperature. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.




Figure 17: Radiance Differences in BRT




Figure 18: Radiance Differences in BRT




Figure 19: Radiance Differences in BRT




Figure 20: Radiance Differences in BRT




Figure 21: Radinace Differences in BRT