

IASI L0 and L1 Daily Monitoring Report **Metop-B**

IASI monitoring team

22/04/2024 00:00:00 - 23/04/2024 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-B satellite retrieved from the IASI L0 and L1 ENG product (3 minutes data packet) for 22/04/2024 00:00:00 - 23/04/2024 00:00:00 .

The monitoring data are extracted on PDU basis.

2 Data quantity 22/04/2024 00:00:00 - 23/04/2024 00:00:00

Product Type	Number	Action
L0 HKTU PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	480	-
L1 DPX PDUs (RM: IASI-HIRS)	0	e
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	9827	9832	20240422093352.059	20240422093354.656
PX1 (130)	8566	8578	20240422191048.209	20240422191052.319
PX1 (130)	5028	5048	20240422223332.733	20240422223338.568
PX2 (135)	9827	9832	20240422093352.059	20240422093354.656
PX2 (135)	8566	8578	20240422191048.209	20240422191052.319
PX2 (135)	5028	5048	20240422223332.733	20240422223338.568
PX3 (140)	9827	9832	20240422093352.059	20240422093354.656
PX3 (140)	8566	8578	20240422191048.209	20240422191052.319
PX3 (140)	5028	5047	20240422223332.733	20240422223338.354
PX4 (145)	9826	9832	20240422093351.844	20240422093354.656
PX4 (145)	8566	8578	20240422191048.209	20240422191052.319
PX4 (145)	5028	5047	20240422223332.733	20240422223338.354
IMG (150)	2210	2219	20240422093351.844	20240422093354.442
IMG (150)	1874	1890	20240422191048.209	20240422191052.319
IMG (150)	4419	4443	20240422223332.518	20240422223338.354
VER (160)	2845	2851	20240422093344.278	20240422093340.278
VER (160)	8096	8102	20240422191040.209	20240422191056.209
VER (160)	15701	15707	20240422223328.193	20240422223344.193
AUX (180)	10383	10385	20240422093344.711	20240422093340.707

Continued on next page

Table 2 – continued from previous page

APID	Seq from	Seq to	Time from	Time to
AUX (180)	14710	14712	20240422191040.643	20240422191056.643
AUX (180)	16231	16233	20240422223328.623	20240422223344.623

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
22/04/2024 00:00:05	-	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	480	-
GQisFlagQual set (PX1)	99.62 %	-
GQisFlagQual set (PX2)	99.68 %	-
GQisFlagQual set (PX3)	99.68 %	-
GQisFlagQual set (PX4)	99.61 %	-
GQisFlagQual set (all)	99.65 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: Timeseries of flag of Over and Under Flows

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class).

A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T, water vapor and Ozone. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used.

Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 28 to 34, the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixels and scan positions 10 to 20) and the average bias OBS-CAL (over all pixels and scan positions 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BT: All Channels




Figure 11: Radiance Anomaly in BT: IASI Band 1




Figure 12: Radiance Anomaly in BT: IASI Band 2




Figure 13: Radiance Anomaly in BT: IASI Band 3




Figure 14: Radiance Anomaly in BT: CO2 14




Figure 15: Radiance Anomaly in BT: CO2 4.3




Figure 16: Radiance Anomaly in BT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board Metop is performed on all pixels with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference NeDT. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.




Figure 17: Radiance Differences in BT




Figure 18: Radiance Differences in BT




Figure 19: Radiance Differences in BT




Figure 20: Radiance Differences in BT




Figure 21: Radinace Differences in BT