

# IASI L0 and L1 Daily Monitoring Report **Metop-C**

IASI monitoring team

02/12/2025 00:00:00 - 03/12/2025 00:00:00

## 1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-C satellite retrieved from the IASI L0 and L1 ENG product (3 minutes data packet) for 02/12/2025 00:00:00 - 03/12/2025 00:00:00 .

The monitoring data are extracted on PDU basis.

## 2 Data quantity 02/12/2025 00:00:00 - 03/12/2025 00:00:00

Product Type	Number	Action
L0 HKTU PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSSGranule	481	-
<b>L1 DPX PDUs (RM: IASI-HIRS)</b>	<b>0</b>	<b>e</b>
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	-	-	-	-
PX2 (135)	-	-	-	-
PX3 (140)	12432	12434	20251202233758.064	20251202233758.497
PX4 (145)	-	-	-	-
IMG (150)	-	-	-	-
VER (160)	16382	0	20251202005932.432	20251202005940.432
VER (160)	3	16383	20251202005940.432	20251202005940.432
VER (160)	-1	4	20251202005940.432	20251202005948.432
VER (160)	16379	0	20251202153316.357	20251202153324.357
VER (160)	0	16380	20251202153324.357	20251202153324.357
VER (160)	-1	1	20251202153324.357	20251202153332.357
VER (160)	16380	0	20251202225012.338	20251202225020.338
VER (160)	1	16381	20251202225020.338	20251202225020.338
VER (160)	-1	2	20251202225020.338	20251202225028.338
AUX (180)	-	-	-	-

Table 2: L0 data gaps

### 3 Instrument modes


Time	Transition from	Transition to
02/12/2025 00:00:04	-	Normal operation

Table 3: Instrument modes

### 4 L0 and L1 Data Quality


Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	481	-
GQisFlagQual set (PX1)	99.64 %	-
GQisFlagQual set (PX2)	99.69 %	-
GQisFlagQual set (PX3)	99.70 %	-
GQisFlagQual set (PX4)	99.61 %	-
GQisFlagQual set (all)	99.66 %	-

Table 4: Quality flags



CMV 2025 Dec 03 07:40:31

Figure 1: L1C data quality



CMV 2025 Dec 03 07:40:34

Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: Timeseries of flag of Over and Under Flows

## 5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class).

A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T, water vapor and Ozone. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used.

Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 28 to 34, the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixels and scan positions 10 to 20) and the average bias OBS-CAL (over all pixels and scan positions 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BT: All Channels




Figure 11: Radiance Anomaly in BT: IASI Band 1




Figure 12: Radiance Anomaly in BT: IASI Band 2




Figure 13: Radiance Anomaly in BT: IASI Band 3




Figure 14: Radiance Anomaly in BT: CO2 14




Figure 15: Radiance Anomaly in BT: CO2 4.3




Figure 16: Radiance Anomaly in BT: O3