

IASI L0 and L1 Daily Monitoring Report **Metop-C**

IASI monitoring team

24/01/2026 00:00:00 - 25/01/2026 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-C satellite retrieved from the IASI L0 and L1 ENG product (3 minutes data packet) for 24/01/2026 00:00:00 - 25/01/2026 00:00:00 .

The monitoring data are extracted on PDU basis.

2 Data quantity 24/01/2026 00:00:00 - 25/01/2026 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	0	e
L0 IASI PDUs	0	e
L1 ENG PDUs	0	e
L1 ENG distinct GEPSGranule	0	a
L1 DPX PDUs (RM: IASI-HIRS)	0	e
L1 DPS Files (RM: OBS-CAL NWP based)	0	e

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	-	-	-	-
PX2 (135)	-	-	-	-
PX3 (140)	-	-	-	-
PX4 (145)	-	-	-	-
IMG (150)	-	-	-	-
VER (160)	-	-	-	-
AUX (180)	-	-	-	-

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
-	-	-

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	0	e
L1 ENG PDUs	0	e
L1 ENG distinct GEPSGranule	0	a
GQisFlagQual set (PX1)	-	-
GQisFlagQual set (PX2)	-	-
GQisFlagQual set (PX3)	-	-
GQisFlagQual set (PX4)	-	-
GQisFlagQual set (all)	-	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows



Figure 3: Level 0 and 1C overall quality



Figure 4: Level 1C quality



Figure 5: Timeseries of flag of Over and Under Flows

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class).

A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T, water vapor and Ozone. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used.

Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 28 to 34, the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixels and scan positions 10 to 20) and the average bias OBS-CAL (over all pixels and scan positions 10 to 20) of the last 30 days.



Figure 6: Average Radiance differences: OBS-CAL



Figure 7: Standard Deviation of Radiance differences



Figure 8: Average Radiance differences: OBS-CAL



Figure 9: Standard Deviation of Radiance differences



Figure 10: Radiance Anomaly in BT: All Channels



Figure 11: Radiance Anomaly in BT: IASI Band 1



Figure 12: Radiance Anomaly in BT: IASI Band 2



Figure 13: Radiance Anomaly in BT: IASI Band 3



Figure 14: Radiance Anomaly in BT: CO2 14



Figure 15: Radiance Anomaly in BT: CO2 4.3




Figure 16: Radiance Anomaly in BT: O3