

IASI L0 and L1 Daily Monitoring Report **Metop-B**

IASI monitoring team

17/02/2026 00:00:00 - 18/02/2026 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-B satellite retrieved from the IASI L0 and L1 ENG product (3 minutes data packet) for 17/02/2026 00:00:00 - 18/02/2026 00:00:00 .

The monitoring data are extracted on PDU basis.

2 Data quantity 17/02/2026 00:00:00 - 18/02/2026 00:00:00

Product Type	Number	Action
L0 HKTU PDUs	481	-
L0 IASI PDUs	480	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSSGranule	473	-
L1 DPX PDUs (RM: IASI-HIRS)	0	e
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	9492	9531	20260217182935.514	20260217182945.460
PX1 (130)	9584	10263	20260217182959.948	20260217183300.049
PX2 (135)	9492	9530	20260217182935.514	20260217182945.245
PX2 (135)	9584	10263	20260217182959.948	20260217183300.049
PX3 (140)	9492	9529	20260217182935.514	20260217182945.026
PX3 (140)	9584	10263	20260217182959.948	20260217183300.049
PX4 (145)	9491	9529	20260217182935.300	20260217182945.026
PX4 (145)	9584	10263	20260217182959.948	20260217183300.049
IMG (150)	15815	15856	20260217182935.300	20260217182944.811
IMG (150)	15920	303	20260217182959.948	20260217183300.049
VER (160)	16102	16108	20260217182933.350	20260217182949.350
VER (160)	16117	16228	20260217182957.350	20260217183301.346
AUX (180)	9772	9774	20260217182933.784	20260217182949.784
AUX (180)	9775	9798	20260217182957.784	20260217183301.780

Table 2: L0 data gaps

3 Instrument modes


Time	Transition from	Transition to
17/02/2026 00:00:03	-	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality


Flag	Value	Action
L0 IASI PDUs	480	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	473	-
GQisFlagQual set (PX1)	99.69 %	-
GQisFlagQual set (PX2)	99.74 %	-
GQisFlagQual set (PX3)	99.76 %	-
GQisFlagQual set (PX4)	99.66 %	-
GQisFlagQual set (all)	99.71 %	-

Table 4: Quality flags



CM 2026 Feb 18 07:40:29

Figure 1: L1C data quality



CM 2026 Feb 18 07:40:33

Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: Timeseries of flag of Over and Under Flows

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class).

A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T, water vapor and Ozone. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used.

Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 28 to 34, the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixels and scan positions 10 to 20) and the average bias OBS-CAL (over all pixels and scan positions 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BT: All Channels




Figure 11: Radiance Anomaly in BT: IASI Band 1




Figure 12: Radiance Anomaly in BT: IASI Band 2




Figure 13: Radiance Anomaly in BT: IASI Band 3




Figure 14: Radiance Anomaly in BT: CO2 14




Figure 15: Radiance Anomaly in BT: CO2 4.3




Figure 16: Radiance Anomaly in BT: O3

6 IASI-HIRS radiance comparison Channel 1-19

The radiance comparison of IASI and HIRS/4 on-board Metop is performed on all pixels with distances smaller than 3 km between IASI and HIRS. All sky conditions are covered. The radiance differences IASI - HIRS are given in brightness temperatures at 280K reference NeDT. All conditions (clear, cloudy, day and night) are given in red in the following figures. The clear sky conditions at night are given in green and the clear sky cases during daylight are displayed in blue.




Figure 17: Radiance Differences in BT




Figure 18: Radiance Differences in BT




Figure 19: Radiance Differences in BT




Figure 20: Radiance Differences in BT




Figure 21: Radinace Differences in BT