

# IASI L0 and L1 Daily Monitoring Report **Metop-C**

IASI monitoring team

28/04/2026 00:00:00 - 29/04/2026 00:00:00

## 1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-C satellite retrieved from the IASI L0 and L1 ENG product (3 minutes data packet) for 28/04/2026 00:00:00 - 29/04/2026 00:00:00 .

The monitoring data are extracted on PDU basis.

## 2 Data quantity 28/04/2026 00:00:00 - 29/04/2026 00:00:00

Product Type	Number	Action
L0 HKTM PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	474	-
L1 ENG distinct GEPSGranule	456	a
L1 DPX PDUs (RM: IASI-HIRS)	0	e
L1 DPS Files (RM: OBS-CAL NWP based)	474	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	-	-	-	-
PX2 (135)	-	-	-	-
PX3 (140)	-	-	-	-
PX4 (145)	-	-	-	-
IMG (150)	-	-	-	-
VER (160)	16380	0	20260428060929.516	20260428060937.516
VER (160)	1	16381	20260428060937.516	20260428060937.516
VER (160)	-1	2	20260428060937.516	20260428060945.516
VER (160)	16382	0	20260428134441.469	20260428134449.469
VER (160)	3	16383	20260428134449.469	20260428134449.469
VER (160)	-1	4	20260428134449.469	20260428134457.469
AUX (180)	-	-	-	-

Table 2: L0 data gaps

### 3 Instrument modes


Time	Transition from	Transition to
28/04/2026 00:00:11	-	Normal operation
28/04/2026 05:31:55	Normal operation	Auxiliary ASE synchronised
28/04/2026 05:33:47	Auxiliary ASE synchronised	External calibration
28/04/2026 05:37:47	External calibration	Auxiliary ASE synchronised
28/04/2026 05:39:55	Auxiliary ASE synchronised	Normal operation
28/04/2026 07:12:58	Normal operation	Auxiliary ASE synchronised
28/04/2026 07:15:06	Auxiliary ASE synchronised	External calibration
28/04/2026 07:19:06	External calibration	Auxiliary ASE synchronised
28/04/2026 07:20:58	Auxiliary ASE synchronised	Normal operation
28/04/2026 08:54:18	Normal operation	Auxiliary ASE synchronised
28/04/2026 08:56:10	Auxiliary ASE synchronised	External calibration
28/04/2026 09:00:10	External calibration	Auxiliary ASE synchronised
28/04/2026 09:02:18	Auxiliary ASE synchronised	Normal operation
28/04/2026 10:35:22	Normal operation	Auxiliary ASE synchronised
28/04/2026 10:37:30	Auxiliary ASE synchronised	External calibration
28/04/2026 10:41:30	External calibration	Auxiliary ASE synchronised
28/04/2026 10:43:22	Auxiliary ASE synchronised	Normal operation
28/04/2026 12:16:42	Normal operation	Auxiliary ASE synchronised
28/04/2026 12:18:34	Auxiliary ASE synchronised	External calibration
28/04/2026 12:22:34	External calibration	Auxiliary ASE synchronised
28/04/2026 12:24:42	Auxiliary ASE synchronised	Normal operation

Table 3: Instrument modes

### 4 L0 and L1 Data Quality


Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	474	-
<b>L1 ENG distinct GEPSSGranule</b>	<b>456</b>	<b>a</b>
GQisFlagQual set (PX1)	98.80 %	-
GQisFlagQual set (PX2)	98.85 %	-
GQisFlagQual set (PX3)	98.84 %	-
GQisFlagQual set (PX4)	98.77 %	-
GQisFlagQual set (all)	98.82 %	-

Table 4: Quality flags



CMV 2026 Apr 29 07:40:29

Figure 1: L1C data quality



CMV 2026 Apr 29 07:40:33

Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: Timeseries of flag of Over and Under Flows

## 5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class).

A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T, water vapor and Ozone. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used.

Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 28 to 34, the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixels and scan positions 10 to 20) and the average bias OBS-CAL (over all pixels and scan positions 10 to 20) of the last 30 days.




Figure 6: Average Radiance differences: OBS-CAL




Figure 7: Standard Deviation of Radiance differences




Figure 8: Average Radiance differences: OBS-CAL




Figure 9: Standard Deviation of Radiance differences




Figure 10: Radiance Anomaly in BT: All Channels




Figure 11: Radiance Anomaly in BT: IASI Band 1




Figure 12: Radiance Anomaly in BT: IASI Band 2




Figure 13: Radiance Anomaly in BT: IASI Band 3




Figure 14: Radiance Anomaly in BT: CO2 14




Figure 15: Radiance Anomaly in BT: CO2 4.3




Figure 16: Radiance Anomaly in BT: O3