

IASI L0 and L1 Daily Monitoring Report **Metop-C**

IASI monitoring team

03/06/2026 00:00:00 - 04/06/2026 00:00:00

1 Introduction

This report provides summary monitoring plots and figures from IASI instrument on the Metop-C satellite retrieved from the IASI L0 and L1 ENG product (3 minutes data packet) for 03/06/2026 00:00:00 - 04/06/2026 00:00:00 .

The monitoring data are extracted on PDU basis.

2 Data quantity 03/06/2026 00:00:00 - 04/06/2026 00:00:00

Product Type	Number	Action
L0 HKTU PDUs	481	-
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	481	-
L1 DPX PDUs (RM: IASI-HIRS)	0	e
L1 DPS Files (RM: OBS-CAL NWP based)	480	-

Table 1: Data quantity

APID	Seq from	Seq to	Time from	Time to
PX1 (130)	6104	6320	20260603162452.997	20260603162551.805
PX2 (135)	6104	6320	20260603162452.997	20260603162551.805
PX3 (140)	6104	6320	20260603162452.997	20260603162551.805
PX4 (145)	6104	6320	20260603162452.997	20260603162551.805
IMG (150)	8753	9000	20260603162452.997	20260603162551.591
VER (160)	16379	0	20260603092653.060	20260603092701.060
VER (160)	0	16380	20260603092701.060	20260603092701.060
VER (160)	-1	1	20260603092701.060	20260603092709.060
VER (160)	15665	15667	20260603162444.997	20260603162452.997
VER (160)	15668	15706	20260603162452.997	20260603162556.997
VER (160)	16380	0	20260603164349.007	20260603164357.003
VER (160)	1	16381	20260603164357.003	20260603164357.003
VER (160)	-1	2	20260603164357.003	20260603164405.003
AUX (180)	12949	12958	20260603162445.431	20260603162557.430

Table 2: L0 data gaps

3 Instrument modes

Time	Transition from	Transition to
03/06/2026 00:00:06	-	Normal operation

Table 3: Instrument modes

4 L0 and L1 Data Quality

Flag	Value	Action
L0 IASI PDUs	481	-
L1 ENG PDUs	480	-
L1 ENG distinct GEPSGranule	481	-
GQisFlagQual set (PX1)	99.66 %	-
GQisFlagQual set (PX2)	99.67 %	-
GQisFlagQual set (PX3)	99.70 %	-
GQisFlagQual set (PX4)	99.63 %	-
GQisFlagQual set (all)	99.66 %	-

Table 4: Quality flags




Figure 1: L1C data quality




Figure 2: Flag of Over and Under Flows




Figure 3: Level 0 and 1C overall quality




Figure 4: Level 1C quality




Figure 5: Timeseries of flag of Over and Under Flows

5 Radiance monitoring based on NWP

The radiance monitoring compares the IASI measurements (L1C-eps-products) obtained under clear sky situation over sea with modeled radiances. Cloud identification is based on cloud flag of co-located AVHRR L1B data in addition to information from the IASI L1C clustering analysis here only homogenous situations are taken into account (99.0 percent in first class).

A radiative transfer model (RTM) is feed with co-located ECMWF profiles of T, water vapor and Ozone. Between March 2007 and the 18th of May 2010 RTIASI in Version 4.0 is used. After that date the RTTOV model in V9.3 is used.

Information about the SST is obtained from the AVHRR L1B or taken from AVHRR scenes analysis (CGS only). In the following figures 28 to 34, the so-called radiance anomaly is shown. The radiance anomaly is defined as the difference between the quarter daily radiance average OBS-CAL (over all pixels and scan positions 10 to 20) and the average bias OBS-CAL (over all pixels and scan positions 10 to 20) of the last 30 days.



Figure 6: Average Radiance differences: OBS-CAL



Figure 7: Standard Deviation of Radiance differences



Figure 8: Average Radiance differences: OBS-CAL



Figure 9: Standard Deviation of Radiance differences



Figure 10: Radiance Anomaly in BT: All Channels



Figure 11: Radiance Anomaly in BT: IASI Band 1



Figure 12: Radiance Anomaly in BT: IASI Band 2



Figure 13: Radiance Anomaly in BT: IASI Band 3



Figure 14: Radiance Anomaly in BT: CO2 14



Figure 15: Radiance Anomaly in BT: CO2 4.3



Figure 16: Radiance Anomaly in BT: O3